

Enginuity Portable Grid®

Model: HS1500D



40 Foot Sound Attenuated Power Module

- Rental Grade Power Module
- Cummins QSK-50 EPA emissions certified Tier II
- 1500 kW stand-by power
- Cummins PCC 3201 digital paralleling controls
- 277/480 Volts, 60 Hz
- Newage Stamford PMG alternator
- 2500 amp electrically operated breaker with GFI
- Engine driven charging alternator
- Battery isolation switch
- Battery charger
- (4) 8D Batteries
- Block heater with isolation valves

Special Features

- 40 foot ISO container with 4" insulation
- Critical grade insulated silencer
- 73 dB(A) @ 7 feet
- Vertical air discharge
- Air discharge roof screen
- Noise reducing, on demand multiple fans
- Dual Core 50°C (122°F) rated electric drive radiator with vertical discharge
- Cable connection box (breaker safety trip) with shore power connection inside
- External emergency stops
- Onboard battery charger
- Battery box mounted within containment
- 1250 gallon Double Wall UL 142 fuel tank with automatic fuel topping system
- Racor triplex fuel water separator (containment mounted)
- External fueling access

- Fire extinguishers (two)
- AC / DC lighting package on solid state timer (contained fixtures)
- 100 Amp auxiliary power electrical distribution
- Eight service access doors
- Oil and coolant drains with isolation valves
- Digital fuel level display (dual)
- Manual fuel sight gauge top tank mounted
- Document storage box
- Aluminum tread plate in walkways
- Ladder Box (locking)
- 4 service ladders and two stabilizer jacks saddle mounted (locking)
- New tandem axle 40 foot chassis with 10 hole Budd Wheels and radial tires
- Under-slung ladder box
- Full performance tested in all modes prior to shipping
- Complete documentation and "as-built" drawings

*We bring the **grid** to you*