

Enginuity Portable Grid®

Model: HS1550G

45 Foot Sound Attenuated Power Module Rental Grade Natural Gas Power Module

- MTU 16V4000L62 Natural Gas Engine (robust)
- Emission compliant
- 1550 kW operated in Grid Parallel Mode
- Available in 50 Hz or 60 Hz (order specific)
- MTU-MMC digital touch screen controller
- Newage / AVK PMG alternator
- 2500 amp UL Listed breaker
- Engine driven charging alternator
- Battery isolation switch
- Battery charger
- (4) 8D Batteries
- Block heater with isolation valves
- 120% containment of all engine fluids

 **NATURAL GAS**



Special Features

- 45 foot ISO container with 4" insulation
- Critical grade insulated silencer
- 78 dB(A) @ 7 feet, (50 Hz or 60 Hz), 100% load
- Vertical air discharge
- Air discharge roof screen
- Dual Core 50^o C (122^o F) rated electric drive radiator with vertical discharge
- Cable connection box (breaker safety trip) with shore power connection inside
- External emergency stops
- Onboard battery charger
- Battery box mounted within containment
- Fuel gas regulation valves with safety external connection
- Fire extinguishers (two)
- AC / DC lighting package on solid state timer
- 100 Amp auxiliary power electrical distribution
- Oil and coolant drains with isolation valves
- Document storage box
- Aluminum tread plate in walkways
- Optional new tri-axle 45 foot chassis with 10 hole Budd wheels and radial tires
- Service ladders and two stabilizer jacks saddle mounted (locking) with optional chassis
- Full performance tested in all modes prior to shipping
- Complete documentation and "as-built" drawings

*We bring the **grid** to you*